

17" LCD Widescreen (716Sw)

TECHNICAL SPECIFICATIONS	17" LCD Widescreen (716Sw)
• Cabinet Color:	Silver/Black
• Panel:	TFT Active Matrix LCD VIS: 17" wide (16:9), Diagonal Hard Coating (3H), Anti-glare Treatment, 90/75 view angle
• Pixel Pitch:	0.258 mm
• Display Area:	372.5 mm x 209 mm
• Brightness:	250 cd/m ² (typ)
• Contrast Ratio:	1500:1 (DCR)
• Response Time:	8 ms (typ)
• Viewing Angle:	CR > 10 : 140/130, CR > 5 : 160/160
• Compatibility:	VESA VGA, XGA, SVGA, MAC®
• Scanning Frequency:	Horizontal: 36.5 ~ 57.75 KHz - Vertical: 55 Hz ~ 75 Hz
• Pixel Frequency:	65.5 MHz
• Maximum and Recommended Resolutions:	1280 x 720 @ 60 Hz
• Resolutions Supported:	640 x 350 @ 70 Hz, 640 x 480 @ 60/72 75 Hz, 720 x 400 @ 70 Hz, 800 x 600 @ 60/75 Hz, 832 x 624 @ 74.5, 1280 x 720 @ 60 Hz
• Color:	Greater than 16 Millions
• Signal Input:	Analog: 0.7Vp-p (standard), 75 Ω HM, Positive
• Connectors:	Signal: D-Sub 15-pin; Power: 3-pin Plug (Country Std.)
• Power Source:	Internal, 100 ~ 240 VAC, 47 ~ 63 Hz
• Power Consumption:	Power on: < 37 W; Standby: < 1 W
• Plug & Play:	DDC 1/2B/CI
• EPA Energy® Star:	Yes
• User Control:	Auto Adjust, Left/Brightness, Power, Right/Contrast, Menu
• OSD Functions:	Brightness, Contrast, Focus, Clock, H/V Position, Color Temperature, Auto Config, OSD H/V Position, OSD Timeout, Language, Information, Reset, Exit
• OSD Languages:	English, French and Spanish
• Regulations:	cULus, FCC, TUV/S, CE, ISO 13406-2, MPRII, Windows Vista™
• Others Features:	DCB, DCR, VESA 75 mm Wall Mount Compliant*, Kensington Security Slot
• Dimensions (W x H x D mm):	Monitor: 404 x 319 x 210; Carton: 467 x 162 x 389
• Weight:	Net: 3.2 Kg, Gross: 4.2 Kg
• Loading Qty w/pallet:	20' = 840 pcs, 40' Std = 1750 pcs
• Warranty:	3 Years

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.

AOC. Líder mundial en monitores.



17" LCD Widescreen (716Sw)